PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: (11) International Publication Number: WO 98/07897 A1 C23F 17/00, 15/00 // B24B 1/00, C23C (43) International Publication Date: 26 February 1998 (26.02.98) 22/63, C25D 3/38, 3/40, B63H 1/14, 1/28 (81) Designated States: AL, AU, BB, BG, BR, BY, CA, CN, CZ, PCT/AU97/00543 (21) International Application Number: EE, GE, HU, IL, IS, JP, KP, KR, LK, LR, LS, LT, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, RO, SG, SI, 21 August 1997 (21.08.97) (22) International Filing Date: SK, TR, TT, UA, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, (30) Priority Data: DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, 22 August 1996 (22.08.96) ΑU PO 1806 MR, NE, SN, TD, TG). (71)(72) Applicant and Inventor: KEMPIN, Ronald [AU/AU]; 3 Rodgers Place, Bull Creek, W.A. 6149 (AU). **Published** With international search report.

(54) Title: PREVENTION OF MARINE ENCRUSTATION ON BRONZE PROPELLERS

(57) Abstract

From the time that they are immersed into a marine environment, bronze propellers are prone to attack by marine organisms, such as barnacles, coral and algae, which attach themselves to the bronze metallic surface, creating lumps on the propeller, which adversely affect its balance and cause impedance and vibration of the propeller and its boat in the water. Ant-fouling paints are either too toxic for the marine environment of lack smoothness on the surface. These problems have been overcome by a combination of known steps, namely, polishing the propeller to prepare it for electroplating, cleansing to remove all traces of dirt and grease, electroplating with copper to a depth of at least 0.005" or 0.15 mm, followed by spraying with a standard solution (5 %) of sodium hypochlorite and sodium chloride in a suitable container to form a firmly adhering conversion coating of basic cupric chloride and then sealing for at least twenty-four hours. The preferred procedure for polishing is 60# grit size at 3500 sfm for roughing, followed by 180# grit size at 5500 sfm for finishing using grease as a polishing aid. Electroplating with copper to the minimum depth provides a smoothing effect ranging from 70 to 90 per cent. The container in which the hypochlorite spraying is carried out is preferably kept sealed until just before fitting and launching. A life expectancy of five (5) years can be anticipated with minimal maintenance every time the vessel is slipped.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL AM AT AU AZ BA BB BE BF BG BJ CA CF CG CH CI CM CN CU	Albania Armenia Austria Austria Australia Azerbaijan Boania and Herzegovina Barbados Belgium Burkina Faso Bulgaria Benin Brazil Belarus Canada Central African Republic Congo Switzerland Côte d'Ivoire Cameroon China Cuha	ES FI FR GA GB GE GH GR HU IE IL IS FT JP KE KG KP	Spain Pinland Prance Gabon United Kingdom Georgia Ghana Guinea Greece Hungary Ireland Israel Iceland Italy Japan Kenya Kyrgyzstan Democratic People's Republic of Korea	LS LT LU LV MC MD MG MK ML MN MR MW MX NE NL NO NZ PL PT	Lesotho Lithuania Luxembourg Larvia Monaco Republic of Moldova Madagascar The former Yugoslav Republic of Macedonia Mali Mongolia Mauritania Malawi Mexico Niger Netherlands Norway New Zealand Poland Portugal	SI SK SN SZ TD TG TJ TM TR TT UA UG US VN YU ZW	Slovenia Slovakia Senegal Swaziland Chad Togo Tajikistan Turkmenistan Turkey Trinidad and Tobago Ukraine Uganda United States of America Uzbekistan Yugoslavia Zimbabwe
CH CI CM CN	Switzerland Côte d'Ivoire Cameroon	KG KP	Kyrgyzstan Democratic People's Republic of Korea	NO NZ PL	Norway New Zealand Poland		Yugoslavia

PREVENTION OF MARINE ENCRUSTATION ON BRONZE PROPELLERS.

This invention relates to a process for the prevention of marine encrustation on bronze propellers, which include tin bronze, aluminium bronze, silicon-aluminium bronze. nickel-aluminium bronze and manganese bronze propellers. As, in operation, water travels over the propeller blades at high velocity, it is essential for the efficiency of the propeller, that the surface be perfectly smooth, even and true. From the time that they are immersed into a marine environment, bronze propellers are prone to attack by marine organisms, such as barnacles, coral and algae, which attach themselves to the bronze metallic surface, creating lumps on the propeller, which adversely affect its balance and cause impedance and vibration of the propeller and its boat in the water. Various remedies have been tried including anti-fouling paints. One of these paints containing tributyl tin, was so toxic to other economic marine life, such as oysters, that it had to be discontinued. Its successor is so viscous, that its application to the finely polished surface of the bronze leaves brush marks in the form of grooves, which adversely affect the fine balance and vibration free performance of the propeller from day 1. Durability of the anti-fouling paint on the propeller can be as short as 30 days in active marine environments.

10

15

20

25

Accordingly, the inventive process seeks to provide protection from marine encrustation for an extended period of time. The process for the prevention of marine encrustation on bronze surfaces, in particular those of propellers, is characterised by the following steps:-

- (a) The cast propeller is first polished to the propeller production standard.
- (b) The whole polished propeller is then cleansed, to remove all traces of dirt and grease.
- 10 (c) The cleansed propeller is then electroplated with copper to a depth of at least 0.005" or 0.15 mm.
 - (d) The electroplated propeller is then placed in a suitable container and sprayed with a standard solution of sodium hypochlorite.
- (e) The container is then sealed for at least twenty-four hours and preferably kept sealed until just prior to launching.

Thereafter, only minimum maintenance is required, when the vessel is slipped periodically, thus providing a substantial reduction in maintenance

costs.

20

25

The first step in the preparation is polishing. Bronze propellers and associated structure are typically sand cast and require polishing to remove scale. Reference to this procedure may be found in the article " Mechanical Finishing - Polishing and Buffing ". The recommended procedure is 60# grit size at 3500 sfm for

SUBSTITUTE SHEET (RULE 26)

10

15

20

25

roughing, followed by 180# grit size at 5500 sfm for finishing using grease as a polishing aid. The second step in the procedure consists of surface preparation or cleansing to remove all traces of dirt and grease and may consist of one or more of alkaline cleaning by dipping or electrolytic means, vapour degreasing and solvent cleaning in the article 2 " Metal Cleaning -Selection of Cleaning Process ". This surface preparation is also the subject of standard ASTM B281 - " Preparation of Copper and Copper Base Alloys for Electroplating." The third step involves electroplating the cleansed propeller with copper to a depth of at least 0.005" or 0.15 mm. Various salts of copper may be used, but the most common are those of the two alkaline (cyanide and pyrophosphate) baths and the two acid (sulphate and fluoborate) baths. These are variously described in 3 " Copper Plating " by Mattie F. McFadden and are the subject of two standards AMS 2418 and MIL-C-14550 (Ord). As well as providing an appropriate surface for subsequent processing, electroplating with copper enhances the surface by providing a substantial levelling effect ranging from 70 to 90 per cent for a minimum deposition of 0.005" in thickness. The fourth step in the process consists of placing the electroplated propeller in a suitable container and spraying the electroplated surface with sodium

SUBSTITUTE SHEET (RULE 26)

hypochlorite solution. This solution is prepared by

WO 98/07897

4

chlorination of sodium hydroxide (caustic soda) solution

or, alternatively, by electrolysis of a sodium chloride

(common salt) solution and reacting the product of the
anode (chlorine) with the product of the cathode (sodium
hydroxide). Sodium hypochlorite is routinely marketed as a
5% equimolecular solution of sodium chloride and sodium
hypochlorite for the disinfection and sterilisation of
such places as dairies and milking sheds under various
trade names such as Eau de Javelle, Chlorox and Dazzle.
The reactions which take place with the copper surface are
believed to be

15

20

25

A first coating of black cupric oxide is formed, which coating is then converted to a blue-green basic cupric chloride. The basic cupric chloride forms a firmly adherent coating, which resists the encroachment of marine organisms. A life expectancy of five years of effective protection against marine growth has been achieved,

5

providing ultimate thrust to manufacturers' standards, together with precise balance and vibration-free performance.

BIBLIOGRAPHY.

Metals Handbook, 8th Edit., Vol.2-" Heat Treating, Cleaning and Finishing." (ASM, Metals Park, Ohio 1964).

The claims defining the invention are as follow:-

- 1. A process for the prevention of marine encrustation on bronze surfaces, in particular those of propellers, to provide protection from marine activity for an extended period of time, characterised by the following steps:-
- (a) the cast propeller is first polished to the propeller production standard;
- (b) the whole polished propeller is then cleansed, to remove all traces of dirt and grease;
- (c) the cleansed propeller is then electroplated with copper to a depth of at least 0.005" or 0.15 mm;
- 15(d) the electroplated propelle. is then placed in a suitable container and sprayed with a standard solution of sodium hypochlorite;
- (e) the container is then sealed for at least twenty20 four hours.
- A process according to Claim 1, wherein the polishing procedure is 60# grit size at 3500 sfm for roughing,

followed by 180# grit size at 5500 sfm for finishing using grease as a polishing aid.

- 3. A process according to Claim 1, wherein the surface cleansing consists of one or more of alkaline cleaning by dipping or electrolytic means, vapour degreasing and solvent cleaning.
- A process according to Claim 1, wherein the copper electroplating baths are alkaline.
- 5. A process according to Claim 4, wherein the copper electroplating bath is an alkaline cyanide bath.
- 6. A process according to Claim 4, wherein the copper electroplating bath is an alkaline pyrophosphate bath.
- 7. A process according to Claim 1, wherein the copper electroplating baths are acid.
- 8. A process according to Claim 7, wherein the copper electroplating bath is an acid sulphate bath.
- 9. A process according to Claim 7, wherein the copper electroplating bath is an acid fluoborate bath.

8

10. A process according to Claim 1, wherein the container is kept sealed until just prior to launching.

International Application No. PCT/AU 97/00543

Α.	CLASSIFICATION OF SUBJECT MATTER						
Int Cl ⁶ :		C25D 3/38, 3/40, R63H 1/14, 1/28					
in Ci	Int Cl ⁶ : C23F 17/00, 15/00 B24B 1/00, C23C 22/63, C25D 3/38, 3/40, B63H 1/14, 1/28.						
According to	International Patent Classification (IPC) or to both	n national classification and IPC					
В.	FIELDS SEARCHED						
Minimum docu	mentation searched (classification system followed by	classification symbols)					
IPC : C23F	17/00, 15/00, 7/02, B63H 1/14						
	searched other than minimum documentation to the ex above, AU Cl.: 73.156.	tent that such documents are included in	the fields searched				
Electronic data (See attached	base consulted during the international search (name of i sheet)	f data base and, where practicable, search	i terms used)				
c.	DOCUMENTS CONSIDERED TO BE RELEVANT	Γ					
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.				
A	EP 188356 A2, (BARPRO LIMITED), 23 July line 13 and Figure 1).	1-10					
A	GB 823531 A, (SOCIÉTÉ DE CONDENSATI MÉCANIQUES), 11 November 1959, (see page Figures 1 to 8 of the drawings).	1-10					
X	Further documents are listed in the continuation of Box C	X See patent family ar	nnex				
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document defining the general state of the art which is not considered to be of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed invention can be considered to involve an inventive step when the document of particular relevance; the claimed							
Date of the act	ual completion of the international search	Date of mailing of the international sear 2.7 NOV 1997	rch report				
Name and mailing address of the ISA/AU AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No.: (02) 6285 3929 AUSTRALIA Facsimile No.: (02) 6285 3929 Authorized officer A. DAVIES Telephone No.: (02) 6283 2072							

International Application No.

Relevant to claim No. 1-10 ge 3 line 38
1-10 ge 3 line 38
1-10 ge 3 line 38
ge 3 line 38
- I
7o. 35, C25,
io. 19, IES LTD.
0. 108,
see page 2
e 2 line 63
line 17
ge 3 1-10
RI No (s

International Application No. PCT/AU 97/00543

Continuation from Box B

Search on Electronic Data Base.

DERWENT WPAT.

. . . .

SS1: B63H-001/IC OR B63B-059/04/IC OR C23/IC OR C25/IC (1768)

SS2: C23C/IC OR C23D/IC OR C23F/IC OR C23G/IC OR C25D/IC OR C25F/IC (147922)

SS3: 1 OR 2 (149619)

SS4: 3 AND BRONZE (556)

SS5: 3 AND BRONZ: (572)

SS6: 5 AND (NEPTUN: OR MARINE OR MARITIME OR AQUATIC OR SEA OR OCEAN OR SUBMARINE OR UNDERWATER OR SUBAQU: OR SEA (W) WATER OR UNDERSEA) (9)

SS7: C23F-015/00/IC OR C23F-017/00/IC (3155)

SS8: 7 AND (ELECTROPLAT: OR PLAT: OR COPPER: OR CU) (872)

SS9: 5 AND (ELECTROPLAT: OR PLAT: OR COPPER: OR CU) (401)

SS10: 8 AND BRONZ: (14)

SS11: 9 AND (NEPTUN: OR MARINE OR MARITIME OR AQUATIC OR SEA OR OCEAN OR SUBMARINE OR UNDERWATER OR SUBAQU: OR SEA (W) WATER OR UNDERSEA) (4)

SS12: 6 OR 10 OR 11 (23)

SS13: 12 AND 75-95 (20)

(PRE- AND POST- 75-95 PRINTED SEPARATELY)

JAPIO.

SS1: B63H-001/IC OR B63B-059/04/IC OR C23/IC OR C25/IC (712)

SS2: C23C/IC OR C23D/IC OR C23F/IC OR C23G/IC OR C25D/IC OR C25F/IC (92435)

SS3: 1 OR 2 (93114)

SS4: 3 AND BRONZE (151)

SS5: 3 AND BRONZ: (154)

SS6: 5 AND (NEPTUN: OR MARINE OR MARITIME OR AQUATIC OR SEA OR OCEAN OR SUBMARINE OR UNDERWATER OR SUBAQU: OR SEA (W) WATER OR UNDERSEA) (6)

SS7: C23F-015/00/IC OR C23F-017/00/IC (1008)

SS8: 7 AND (ELECTROPLAT: OR PLAT: OR COPPER: OR CU) (298)

SS9: 5 AND (ELECTROPLAT: OR PLAT: OR COPPER: OR CU) (114)

SS10: 8 AND BRONZ: (1)

SS11: 9 AND (NEPTUN: OR MARINE OR MARITIME OR AQUATIC OR SEA OR OCEAN OR SUBMARINE OR UNDERWATER OR SUBAQU: OR SEA (W) WATER OR UNDERSEA) (4)

SS12: 6 OR 10 OR 11 (7)

(7 ABSTRACTS PRINTED)

Information on patent family members

International Application No. PCT/AU 97/00543

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent :	Document Cited in Sea Report	arch		Pat	ent Family Member		
EP	188356 A2	AU US	52410/86 A1 4724107 A	JP	61/217250 A2	NO	860123 A
GB	823531 A	NOT	KNOWN	-			
GB	1299126 A	NOT	KNOWN				
GB	2026039 A1	AU NO	49154/79 A1 792426 A	DK WO	1066/80 A 80/00262 A1	EP	16080 A1
JP	59/197590 A2	NONE					
JP	61/012496 A2	NONE					
JP	06/270322 A2	NONE					
US	3426473 A	DE	1621935 A	ES	338679 A1	FR	1521867 A5
		GB	1185902 A	NL	6704657 A	SE	344313 B
US	3458413 A	DE	16 42486 A	FR	1474268 A5	NL	6602891 A
US	3497434 A	DE	1771835 A	FR	1576662 A	GB	11 7 6274 A
		JP	48/039343 A2	NL	6810165 A	SE	347924 B
US	5080926 A	NONE					
							
							END OF ANNE